

The DJ800 is a municipal grade double jacketed hose with a lightweight EPDM rubber liner that meets all the requirements of NFPA 1961. Its lightweight and durable construction is designed for use as an attack handline hose and is manufactured to a service test pressure of 400 psi to handle all fireground challenges with ease. The tightly woven polyester fabric allows for easy, flat-folding storage. With the DJ800, firefighters can confidently tackle a variety of challenges, from structure fires to industrial accidents.

TEMPERATURE RANGE: -40F to 150F (-40C to 65C)

COUPLINGS: NPSH, Aluminum NH Threads, and Special Threads Available

HOSE COLORS Yellow Red Blue Orange Green White (Coated)

TECHNICAL DATA & INFORMATION									
NOMINAL SIZE	INTERNAL/OUTSIDE DIAMETER				BOWL SIZE	WEIGHT	TESTING PRESSURES (PSI)		
	Dry ID	Charged ID at 50 psi	Charged ID at 150 psi	Charged OD at 150 psi		LBS./50′ Uncoupled	Service	Proof	Burst
1-1/2"	-	-	-	-	1.938"	16	400	800	1200
1-3/4"	-	-	-	-	2.063"	18	400	800	1200
2"	1	-	-	-	2.438"	21	400	800	1200
2-1/2"	1	-	-	-	2.938"	26	400	800	1200
3"	-	-	-	-	3.563"	40	400	800	1200

^{*1-}year warranty.

Warranty Conditions:

The manufacturer warrants the hose to be free from defects in materials and workmanship for a period of ten years. This warranty shall provide for the repair or replacement of hose and couplings proven to have failed due to faulty material or workmanship.

