

FlashPoint forestry hose is a lightweight, all-synthetic fire hose with a polyurethane lining inside a polyester jacket that meets the USDA Forest Service Specification 5100-187 Type II for "Synthetic Lined" fire hose. Designed for easy transport by backpack or by hand, it excels in challenging conditions, making it ideal for long distances over steep or rough terrain in forest environments. Its WearGuard treatment greatly increases abrasion and heat and flame resistance while virtually eliminating water pickup.

Both 1" and 1.5" sizes are available in 50' or 100' feet lengths and include your choice of aluminum rocker lug or quarter- turn forestry couplings.

TEMPERATURE RANGE: -40F to 150F (-40C to 65C)

COUPLINGS: NH, NPSH, or Quarter-Turn Aluminum Coupling

HOSE COLORS

Yellov

TECHNICAL DATA & INFORMATION					
NOMINAL SIZE (INCHES)	BOWL SIZE (INCHES)	SERVICE PSI	PROOF PSI	BURST PSI	WEIGHT (LBS./50' UNCOUPLED)
1"	1.188	300	600	900	4
1-1/2"	1.75	300	600	900	6.5

^{*1-}year warranty.

Warranty Conditions:

The manufacturer warrants the hose to be free from defects in materials and workmanship for a period of one year. This warranty shall provide for the repair or replacement of hose and couplings proven to have failed due to faulty material or workmanship.



^{*1&}quot; &*1-1/2" - Yellow coated meets USDA FSS 5100-187 Type II.